

LAW OFFICES
FINNEGAN, HENDERSON, FARABOW, GARRETT & DUNNER, L.L.P.
1300 I Street, N.W.
Washington, DC 20005

Telephone
(202) 408-4000

Facsimile
(202) 408-4400

FACSIMILE TRANSMITTAL

TO

Name:	Examiner Hiteshew	Phone No.:	571.272.1463
Firm:	United States Patent and Trademark Office	Date:	October 30, 2002
Fax No.:	571.273.1473		
Subject:	U.S. Patent Application Serial No. 10/602,072		

FROM

Name	David M. Longo, Reg. No. 53,235	Phone No.:	202-408-4489
Fax # Verified by:	DML @ MD 749	# Pages (incl. this)	16
Our File No.:	04329.2470-01		

Confirmation Copy to Follow: No

Message:

Further to our conversation earlier today, we attach a copy of the Preliminary Amendment filed on June 24, 2003.

*Please verify that you now have all pages of the Preliminary Amendment.
Thank you.*

If there is a problem with this transmission, notify fax room at (202) 408-4174 or the sender at the number above.

This facsimile is intended only for the individual to whom it is addressed and may contain information that is privileged, confidential, or exempt from disclosure under applicable law. If you have received this facsimile in error, please notify the sender immediately by telephone (collect), and return the original message by first-class mail to the above address.

PATENT
Customer No. 22,852
Attorney Docket No. 04329.2470-01

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:)
Shoji SETA, et al.) Group Art Unit: *Not Yet Assigned*
Cont. of Application No.: 09/739,905) Examiner: *Not Yet Assigned*
Filed: Herewith)
For: DRY ETCHING METHOD AND)
SEMICONDUCTOR DEVICE)
MANUFACTURING METHOD)

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

PRELIMINARY AMENDMENT

Prior to the examination of the above application, please amend this application as follows:

IN THE ABSTRACT:

Please replace the current Abstract with the Substitute Abstract attached on a separate page. The full text of the Abstract in clean form is as follows:

--A dry etching method comprises sequentially laminating a first insulating layer containing carbon and a second insulating layer containing carbon on a substrate, patterning the second insulating layer to form a mask; forming grooves in the first insulating layer by etching the first insulating layer with the second insulating layer used as a mask such that each of the grooves has a side surface and a bottom surface in the first insulating layer; and removing the

FINNEGAN
HENDERSON
FARABOW
GARRETT &
DUNNER LLP
1300 I Street, NW
Washington, DC 20005
202.408.4000
Fax 202.408.4400
www.finnegan.com